

MODEL 230.4

Shown on model 230.4 without code (P99)  
Special model "AMG Black Series"


1 Electrical connectors

N70 Overhead control panel control unit



P82.20-2351-06

☒ ☒	Remove/install		
1  <b>AD</b>	Buffer basic data for overhead control panel control unit (N70) in STAR DIAGNOSIS  Connect STAR DIAGNOSIS and read out fault memory	When installing new overhead control panel control unit (N70). <b>i</b> <b>Installation:</b> Transfer buffered basic data to the new overhead control panel control unit (N70).	<b>AD00.00-P-2000-04A</b>
2	Switch off the ignition and remove the transmitter key from the EIS control unit	<b>i</b> On vehicles with code (889) Keyless-Go, press KEYLESS-GO start/stop button repeatedly until ignition is switched off. Remove Keyless-Go chip card or transmitter key from vehicle and store beyond the reach of the transmitter (at least 2 m).	
3	Unclip overhead control panel control unit (N70) at retaining clamps (arrows)	<b>!</b> Carefully unclip overhead control panel control unit (N70), otherwise this can damage the housing of the overhead control panel control unit (N70). <b>!</b>	<b>*110589035900</b>
4	Separate electrical connectors (1)		
5	Remove the overhead control panel control unit (N70)		
6	Install in the reverse order		



110 589 03 59 00

Mounting wedge